

Page: 1 of 3

Detailed Saleyard Report - Cattle Market information provided by MLA's National Livestock Reporting Service

 Roma Store
 report date
 12/10/2021

 Yarding
 5148
 comparison date
 05/10/2021

 Change
 1729

Numbers rose by 1729 to see a total yarding of 5148 at the Roma Store Sale as intermittent storms passed. The ALPA Queensland Young Auctioneers competition final normally held at the EKKA was incorporated into the sale. Steers accounted for over half of the yarding with cattle drawn from a wide supply area. The overall quality of the yarding was mixed with a good representation of heavy oats finished bullocks and some large single vendor female lines. A larger buying panel was present and operating, including all regular processors. The market remained strong with solid buyer competition on quality cattle and price fluctuations were reflective of quality variations. Light weight steers under 280kg to feed or background improved by 3c/kg. Medium weight yearling steers under 330kg improved by 5c while medium weight steers under 400kg fell by 8c to 23c/kg. Heavy weight steers fell by 3c to 10c/kg. Light weight heifers to restockers fell by 13c to 21c while medium weight heifers under 330kg to restockers improved by 37c/kg. Heavy weight cows improved by 1c to 6c/kg.

Light weight yearling steers under 200kg sold to a top of 698.2c to average 687c/kg. Light weight yearling steers under 280kg to restockers made to 702.2c to average 644c/kg. Medium weight yearling steers under 330kg to restockers sold to 658.2c to average 609c/kg. Medium weight yearling steers under 400kg to feed made to a top of 618.2c to average 569c, while heavy weight yearling steers over 400kg to feed reached a top of 534.2c to average 482c/kg. Light weight yearling heifers under 200kg to restockers reached a top of 692.2c to average 615c/kg. Light weight yearling heifers under 280kg to restockers also made to 654.2c to average 567c/kg. Medium weight yearling heifers under 330kg to feed sold to 598.2c to average 547c while medium weight yearling heifers under 400kg to restockers reached a top of 702.2c to average 702c/kg. Heavy weight yearling heifers over 400kg to feed made to a top of 468.2c to average 455c/kg.

The best of the grown steers made to 417.2c to average 397c while the best of the grown heifers sold to a top of 454.2c to average 439c/kg. A good run of PTIC red tag cows sold at open auction to a top of \$2080/head. Heavy weight 3 score cows reached a top of 369.2c to average 362c while heavy weight 4 score prime cows made to a top of 383.2c to average 379c/kg. Light weight bulls to restockers sold to a top of 668.2c to average 657c/kg. The best of the heavy weight bulls reached a top of 374.2c to average 352c/kg. Cows and calves made to a top of \$2700/unit.

MARKET REPORTER: Sherrill Stivano

Click here to view the new and improved Prime Cattle Market Reports

Category Weight	Sale Prefix	Muscle Score *	Fat Score*	Head	Live Weight c/kg				Estimat	ed Carcas c/kg*	se Weight		Estimated \$/Head		
					Low	High	Avg	Change	Low	High	Avg	Low	High	Avg	
Yearling St	eer														
0-200															
	RS	D	2	63	648.0 -	698.0	687.1	2		-	0	1231	- 1273	1,252	
200-280															
	FD	С	2	158	540.0 -	656.0	607.3	3		-	0	1350	- 1755	1,598	
	RS	С	2	339	542.0 -	702.0	643.6	-4		-	0	1385	- 1815	1,549	
280-330															
	FD	C	2	378	494.0 -	600.0	562.3	5		-	0	1511	- 1875	1,722	
	RS	C	2	380	548.0 -	658.0	609.5	5		-	INESTO O AUSTRA	1686	- 2009	1,834	
330-400															
	FD	С	2	167	454.0 -	600.0	527.2	-23		-	0	1612	- 2262	1,873	
	RS	С	2	131	470.0 -	618.0	568.9	-8		-	0	1669	- 2090	1,959	
400+															
	FD	С	_2	343	412.0 -	534.0	482.1	-10		-	0	1868	- 2503	2,216	
	PR	С	MEA 2 LIVES	45	410.0 -	425.0	423.3	N/Q	759	- 787	784	2235	- 2465	2,439	
	PR	С	3	191	412.0 -	450.0	425.5	-3	763	- 833	788	2130	- 2912	2,479	
				2195	410.0	702.0			759	833		1231	2912		
Yearling He 0-200	eifer														
	RS	D	2	143	530.0	692.0	614.6	-21		- MEAT 8	O	875	- 1349	1,114	
200-280															

© 2021 Meat and Livestock Australia Limited

Click here to view the new and improved Prime Cattle Market Reports

FD	Category Weight	Sale Prefix	Muscle Score *	Fat Score*	Head		Live Wei	ght c/kg	Estimated Carcase Weight c/kg*						Estimated \$/Head		
PR C 2 2 73 460.0 - 492.0 479.3 52 852 - 911 888 1107 - 1196 1.1 PR D 2 10 396.0 - 396.0 396.0 NO 396.0 NO 733 - 733 733 1009 - 1669 1.0 RS C 2 277 458.0 - 654.0 566.9 -13 - 733 - 733 733 1009 - 1669 1.0 RS C 2 277 458.0 - 654.0 566.9 -13 - 733 - 733 733 1009 - 1609 1.0 RS C 2 2 45 418.0 574.0 481.7 52 0 1296 - 1609 1.0 PR C 2 2 9 400.0 - 426.0 412.1 42 741 - 789 763 1146 - 1280 1107 1107 1.1 RS C 2 2 78 472.0 - 598.0 547.2 37 0 1368 - 1911 1.6 RS C 2 2 157 410.0 - 566.0 430.2 - 103 0 1368 - 1911 1.6 RS C 2 1 19 702.0 - 702.0 702.0 1219 0 1368 - 1911 1.6 RS C 2 1 19 702.0 - 702.0 702.0 1219 0 1520 1359 1.3 RS C 2 2 4 382.0 - 382.0 382.0 321 707 - 707 707 1547 - 1547 1.5 PR C 2 4 382.0 - 382.0 382.0 321 707 - 707 707 1547 - 1547 1.5 PR C 3 4 396.0 702.0 702.0 702.0 702.0 700 700 700 1985 - 1985 1.9 RS C 2 2 6 400.0 - 408.0 455.3 35 0 1828 - 1989 1.9 RS C 2 2 6 400.0 - 408.0 455.3 35 0 1828 - 1989 1.9 RS C 2 2 6 400.0 - 408.0 455.3 35 0 1820 - 1828 1.9 RS C 3 1 1 390.0 - 433.0 400.0 N/Q 700 - 702 702 702 702 702 702 702 702 702 702			4			Low	High	Avg	Change	Low		High	Avg	Low	High	Avg	
PR D 2 1 10 396.0 - 396.0 396.0 N/O 733 - 733 733 1069 - 1069 1.0 PS C 2 277 458.0 - 654.0 566.9 -13 - 0 0 1115 - 1602 1.3 BO 330 PD C 2 45 418.0 - 574.0 481.7 52 - 0 0 1296 - 1280 1.2 PR C 2 2 94 400.0 - 426.0 412.1 42 741 - 789 763 1146 - 1280 1.2 PR D 2 8 346.0 346.0 N/O 641 - 641 641 1107 - 1107 1.1 RS C 2 157 410.0 - 566.0 430.2 103 - 0 0 1368 - 1911 1.6 BD C 2 157 410.0 - 566.0 430.2 103 - 0 0 1368 - 1911 1.6 BD C 2 157 410.0 - 566.0 430.2 103 - 0 0 2352 2.3 BD D D 2 5 394.0 394.0 394.0 N/O 2 19 - 0 0 1368 - 1913 1.5 PD D 2 5 394.0 394.0 394.0 N/O 2 19 - 0 0 2352 2.3 BD D C 2 19 702.0 702.0 702.0 129 - 0 0 2352 2.3 BD P C 2 2 19 402.0 430.0 423.9 -17 - 0 1628 - 1828 1.7 PR C 2 4 382.0 382.0 382.0 382.0 382.0 381.0 107 700 700 1985 - 1985 1.9 PR C 2 3 4 382.0 382.0 382.0 378.0 N/O 700 - 700 700 1985 - 1985 1.9 PR C 2 3 6 400.0 702.0 702.0 1641 911 - 875 2.352 FD D C 2 2 27 410.0 - 420.0 415.3 N/O 700 - 700 700 1985 - 1985 1.9 PR C 3 3 1 233.0 423.0 423.0 N/O 700 - 700 700 1985 - 1985 1.9 BD C 3 3 1 233.0 423.0 423.0 N/O 700 - 700 700 1985 - 1985 1.9 PR C 3 3 1 233.0 423.0 423.0 N/O 737 - 752 749 2070 - 2071 2.0 BD C 5 96 3 18 376.0 423.0 423.0 N/O 738 - 752 749 2070 - 2071 2.0 BD C 5 97 376.0 423.0 423.0 N/O 738 - 752 749 2070 - 2071 2.0 BD C 5 98 C 3 18 376.0 423.0 423.0 N/O 738 - 752 749 2070 - 2071 2.0 BD C 5 98 C 3 18 376.0 423.0 423.0 N/O 738 - 752 749 2070 - 2071 2.0 BD C 5 98 C 3 18 376.0 423.0 N/O 738 - 752 749 2070 - 2071 2.0 BD C 5 98 C 3 18 376.0 443.0 N/O 738 - 752 749 2070 - 2071 2.0 BD C 5 98		FD	TRALIA C	2	18	416.0 -	570.0	458.8	-61		-		O AUSTRALI	1144	- 1539	1,254	
88 C 2 2 277 458.0 - 654.0 566.9 -13		PR	С	2	73	460.0 -	492.0	479.3	52	852	-	911	888	1107	- 1196	1,142	
80-330 PD C 2 45 418.0 - 574.0 481.7 -52 - 0 1296 - 1837 1.4 PR C 2 29 400.0 - 426.0 412.1 42 741 - 789 763 1146 - 1837 1.4 PR C 2 2 78 472.0 - 598.0 547.2 37 - 0 1368 - 1911 1.6 RS C 2 78 472.0 - 598.0 547.2 37 - 0 1368 - 1911 1.6 RS C 2 157 410.0 - 566.0 430.2 - 103 - 0 1415 - 1953 1.5 PD C 2 157 410.0 - 566.0 430.2 - 103 - 0 1415 - 1953 1.5 PD D 2 5 394.0 - 394.0 394.0 N/Q - 0 1359 - 1359 1.3 RS C 2 19 702.0 - 702.0 702.0 702.0 719 - 0 2352 - 2352 2.3 00+ PR C 2 4 382.0 - 382.0 382.0 -31 707 - 707 707 1547 - 1547 1.5 PR C 3 4 378.0 - 378.0 378.0 N/Q 700 - 700 700 1965 - 1985 1.9 PR C 3 44.00 702.0 - 400.0 400.0 N/Q - 0 1520 - 1520 1.5 00-500 PD C 2 2 6 400.0 - 400.0 400.0 N/Q - 0 1520 - 1520 1.5 00-500 PR C 3 11 396.0 - 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 735 2500 - 2507 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 772 752 742 740 200 - 200 750 2.0 00-500 PR C 3 18 376.0 417.0 396.8 177 696 770 700 700 700 700 700 700 700 700 70		PR	D	2	10	396.0 -	396.0	396.0	N/Q	733	-	733	733	1069	- 1069	1,069	
FD C 2 45 418.0 - 574.0 481.7 52		RS	С	2	277	458.0 -	654.0	566.9	-13		-		0	1115	- 1602	1,373	
PR C 2 2 9 400.0 - 426.0 412.1 42 741 - 789 763 1146 - 1280 1.2 PR D 2 8 346.0 - 346.0 346.0 N/O 641 - 641 641 1107 - 1107 1.1 RS C 2 78 472.0 - 598.0 547.2 37 - 0 1368 - 1911 1.6 RS C 2 157 410.0 - 566.0 430.2 -103 - 0 1415 - 1953 1.5 FD D C 2 157 410.0 - 566.0 430.2 -103 - 0 1415 - 1953 1.5 FD D C 2 19 702.0 - 702.0 702.0 702.0 219 - 0 2352 - 2352 2.3 00+ FD C 2 2 4 382.0 - 382.0 382.0 -31 707 - 707 707 1547 - 1547 1.5 PR C 3 4 378.0 - 378.0 378.0 N/O 700 700 700 1965 - 1965 1.9 RS C 2 6 3 44.00.0 - 466.0 455.3 35 - 0 1828 1.9 PG D C 2 6 400.0 - 400.0 400.0 N/O - 0 1520 - 1520 1.5 00-500 FD C 2 2 7 410.0 - 420.0 413.3 N/O - 0 1520 - 1520 1.5 00-750 PR C 3 18 376.0 423.0 423.0 N/O 733 - 783 783 2200 - 2200 2.2 00-750 PR C 3 18 376.0 417.0 396.8 -17 696 772 735 2500 - 2585 2.5 50+ PR C 3 18 376.0 417.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 398.0 - 400.0 390.0 N/O 722 - 722 722 3120 - 3120 3.1 FD D 2 10 396.0 - 400.0 390.0 N/O 722 - 722 722 722 3120 - 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 2 10 396.0 - 400.0 396.8 -17 696 783 1520 3120 3.1 FD D 3 2 100 - 300.0 300.0 300.0 N/O 70 - 0 1050 2 1005 2400 2.4 FD D 3 3 44 360.0 - 404.0 384.6 0 679 762 762 766 1307 - 1773 1.5 FD D 3 400.0 - 400.0 444.0 0 444.0 0 444.0 0 444.0 0 164.0 0 679 762 762	280-330																
PR D 2 8 346.0 - 346.0 346.0 N/O 641 - 641 641 1107 - 1107 1,1 RS C 2 78 472.0 - 598.0 547.2 37 - 0 1368 - 1911 1,6 RS C 2 157 410.0 - 566.0 430.2 -103 - 0 1368 - 1911 1,6 RS C 2 157 410.0 - 566.0 430.2 -103 - 0 1359 - 1359 1,3 RS C 2 19 702.0 - 702.0 702.0 219 - 0 1529 - 1359 1,3 RS C 2 19 702.0 - 702.0 702.0 219 - 0 1628 - 1828 1,7 PR C 2 4 382.0 - 382.0 382.0 -31 707 - 707 707 1547 - 1547 1,5 PR C 3 4 378.0 - 378.0 378.0 N/O 700 - 700 700 1985 - 1985 1,9 RS C 2 6 4 400.0 - 468.0 455.3 35 - 0 1828 1999 1,9 RS C 2 7 410.0 - 420.0 413.3 N/O - 0 1520 - 1520 1,5 RS C 2 7 410.0 - 420.0 413.3 N/O - 0 1520 - 1520 1,5 RS C 3 1 4 398.0 - 460.0 404.3 N/O 737 - 752 749 2070 - 2071 2,0 RS C 3 1 4 398.0 - 406.0 404.3 N/O 737 - 752 749 2070 - 2071 2,0 RS C 3 1 4 398.0 - 406.0 404.3 N/O 737 - 752 749 2070 - 2071 2,0 RS C 3 1 3 30.0 - 423.0 N/O 783 - 783 783 2200 - 2200 2,2 RS C 3 1 1 390.0 - 390.0 390.0 N/O 783 - 783 783 2200 - 2585 2,5 RS C 3 1 1 390.0 - 390.0 390.0 N/O 783 - 783 783 2200 - 2585 2,5 RS C 3 1 1 390.0 - 390.0 390.0 N/O 722 - 722 722 3120 - 3120 3,1 RS C 3 1 1 390.0 - 390.0 390.0 N/O 722 - 722 722 3120 - 3120 3,1 RS C 3 2 375.0 - 375.0 375.0 N/O 708 - 762 726 1307 - 1777 1,773 1,8 RS D 2 2 3 300.0 - 454.0 439.1 N/O 0 1502 - 1605 1,0 RS D 3 60 390.0 454.0 439.1 N/O 0 1502 - 1005 - 1005 - 1005 RS D 3 60 390.0 454.0 439.1 N/O 0 1502 - 1005 - 1005 - 1005 RS D 3 60 390.0 454.0 439.1 N/O 0 1502 - 1005 - 1005 - 1005 RS D 3 60 390.0 454.0 439.1 N/O 0 1502 - 1005 - 1005 - 1005 RS D 3 60 390.0 454.0 439.1 N/O 0 1502 - 1005 - 1005 - 1005 RS D 3 60 390.0 454.0 439.1 N/O 0 1502 - 1005 - 1005 - 1005 RS D 3 60 390.0 454.0 439.1 N/O 0 1502 - 1005 - 1005 - 1005 RS D 3 60 390.0 454.0 439.1 N/O 0 1502 - 1005 - 2400 RS D 3 60 300.0 454.0 649.1 N/O 0 1502 - 1005 - 2400 RS D 3 60 300.0 454.0 649.0 139.1 N/O 0 1502 - 1005 - 2400 RS D 3 60 300.0 454.0 669.0 1300 N/O 0 1502 - 1005 - 2400 RS D 3 60 300.0 454.0 669.0 1300 N/O 0 1502 - 1005 - 2400 RS D 3 60 300.0 454.0 669.0 1300 N/O -											-		0			1,492	
RS C 2 16 472.0 - 598.0 547.2 37 - 0 1368 - 1911 1.6 30-400 FD C 2 157 410.0 - 566.0 430.2 -103 - 0 1415 - 1953 1.5 FD D 2 5 394.0 - 394.0 394.0 N/Q - 0 1359 - 1359 1.35 RS C 2 19 702.0 - 702.0 702.0 702.0 129 - 0 2352 - 2352 2.3 00+ FD C 2 2 94 402.0 - 430.0 423.9 -17 - 0 1628 - 1828 1.7 PR C 2 4 382.0 - 382.0 382.0 382.0 -31 707 - 707 707 1547 - 1547 1.5 PR C 3 4 382.0 - 386.0 378.0 N/Q 700 - 700 700 1985 - 1985 1.9 RS C 2 6 400.0 - 468.0 455.3 35 - 0 1828 - 1989 1.9 FD C 2 6 400.0 - 400.0 400.0 N/Q - 0 1520 - 1520 1.5 00-500 FD C 2 7 410.0 - 420.0 413.3 N/Q - 0 0 1804 - 1953 1.8 00-600 PR C 3 1 438.0 - 406.0 404.3 N/Q 737 - 752 749 2070 - 2071 2.0 PR C 3 1 1 423.0 - 423.0 N/Q 783 - 783 783 2200 - 2200 2.2 00-750 PR C 3 113 390.0 - 403.0 423.0 N/Q 783 - 783 783 2200 - 2585 2.5 50+ PR C 3 113 390.0 - 390.0 390.0 N/Q 722 - 722 722 722 3120 - 3120 rrown Helfer -540 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 0 1502 - 1005 1.0 RS D 3 3 43 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1.5 RS D 3 3 60 390.0 - 454.0 384.6 0 679 - 762 726 1307 - 1773 1.5 RS D 3 3 60 390.0 - 454.0 384.6 0 679 - 762 726 1307 - 1773 1.5 RS D 3 3 60 390.0 454.0 439.1 N/Q - 0 0 1502 - 1907 1.8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2.4 108 300.0 454.0 679 762 1005 2400											-					1,223	
30-400 FD										641	-	641	641			1,10	
FD C 2 157 410.0 - 566.0 430 2 -103 - 0 1415 - 1953 1.5 FD D 2 5 394.0 - 394.0 394.0 N/Q - 0 1359 - 1359 1.3 RS C 2 19 702.0 - 702.0 702.0 219 - 0 2352 - 2352 2.3 COO+ FD C 2 29 402.0 - 430.0 423.9 -17 - 0 1628 - 1828 1.7 PR C 3 4 382.0 - 318.0 382.0 382.0 382.0 -31 707 - 707 707 1547 - 1547 1.5 PR C 3 4 382.0 - 468.0 455.3 35 - 0 1828 1.9 PR C 3 4 394.0 702.0 - 641 911 875 2352 - 2352 2.3 COO+ FD C 2 2 6 400.0 - 400.0 400.0 N/Q - 0 1520 - 1520 1.5 COO-500 FD C 2 14 398.0 - 406.0 404.3 N/Q 737 - 752 749 2070 - 2071 2.0 PR C 3 1 4 398.0 - 406.0 404.3 N/Q 737 - 752 749 2070 - 2071 2.0 PR C 3 1 3 18 376.0 - 417.0 396.8 -17 696 - 772 735 2500 - 2585 2.5 COO-500 PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 3.1 TOWN Helfer -540 FD D D 2 10 398.0 - 400.0 398.2 N/Q 722 - 722 722 3120 - 3120 3.1 TOWN Helfer -540 FD D 3 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 454.0 439.1 N/Q - 0 1502 - 1907 1.8 A0+ PR C 3 2 755.0 375.0 375.0 N/Q 708 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 454.0 439.1 N/Q - 0 1502 - 1907 1.8 A0+ PR C 3 2 755.0 375.0 375.0 N/Q 708 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 454.0 439.1 N/Q - 0 1502 - 1907 1.8 A0+ PR C 3 2 755.0 375.0 375.0 N/Q 708 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 454.0 439.1 N/Q - 0 1502 - 1907 1.8 A0+ PR C 3 2 755.0 375.0 375.0 N/Q 708 - 708 708 708 2400 2.4 A0+ PR C 3 2 755.0 375.0 375.0 N/Q 708 - 708 708 708 2400 2.4 A0+ PR C 3 2 755.0 375.0 375.0 N/Q 708 - 708 708 708 2400 2.4 A0+ PR C 3 2 755.0 375.0 375.0 N/Q 708 - 708 708 708 2400 2.4 A0+ PR C 3 2 755.0 375.0 375.0 N/Q 708 - 708 708 708 2400 2.4 A0+ PR C 3 2 755.0 375.0 375.0 N/Q 708 - 708 708 708 2400 2.4 A0+ PR C 3 2 755.0 375.0 375.0 N/Q 708 - 708 708 708 2400 2.4 A0+ PR C 3 2 755.0 375.0 375.0 N/Q 708 - 708 708 708 2400 2.4 A0+ PR C 3 2 755.0 375.0 375.0 N/Q 708 - 708 708 708 2400 2.4 A0+ PR C 3 3 2 375.0 375.0 375.0 N/Q 708 - 708 708 708 2400 2.4 A0+ PR C 3 3 2 375.0 375.0 375.0 N/Q 708 - 708 708 708 2400 2.4 A0+ PR C 3 3 2 375.0 375.0 375.0 N/Q 708 -		RS	С	2	78	472.0 -	598.0	547.2	37		-		0	1368	- 1911	1,69	
FD D 2 5 394.0 - 394.0 394.0 N/Q - 0 1359 - 1359 1.3 RS C 2 19 702.0 - 702.0 702.0 219 - 0 2352 - 2352 2.3 00+ FD C 2 29 402.0 - 430.0 423.9 -17 - 0 1628 - 1828 1.7 PR C 2 4 382.0 - 382.0 382.0 31 707 707 707 1547 - 1547 1.5 PR C 3 4 382.0 - 378.0 378.0 N/Q 700 - 700 700 1985 - 1985 1.9 RS C 2 63 430.0 - 468.0 455.3 35 - 0 1828 1989 1.9 RS C 2 6 400.0 - 400.0 400.0 N/Q - 0 1520 - 1520 1.5 00-500 FD C 2 7 410.0 - 420.0 413.3 N/Q - 0 1804 - 1953 1.8 00-600 PR C 3 1 4 398.0 - 406.0 404.3 N/Q 737 - 752 749 2070 - 2071 2.0 PR C 3 1 1 390.0 - 406.0 404.3 N/Q 737 - 752 749 2070 - 2071 2.0 00-750 PR C 3 18 376.0 - 417.0 396.8 - 17 696 - 772 735 2500 - 2585 2.5 50+ PR D 3 343 360.0 - 400.0 390.0 N/Q 722 - 722 722 3120 3120 3120 rown Helfer -540 FD D 2 10 398.0 - 400.0 390.0 N/Q 722 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 - 454.0 439.1 N/Q 700 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 - 454.0 439.1 N/Q 700 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 - 454.0 439.1 N/Q 700 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 - 454.0 439.1 N/Q 700 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 - 454.0 439.1 N/Q 700 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 - 454.0 439.1 N/Q 700 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 - 454.0 439.1 N/Q 700 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 - 454.0 439.1 N/Q 700 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 - 454.0 439.1 N/Q 700 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 - 454.0 439.1 N/Q 700 - 762 726 1307 - 1773 1.5	330-400	/ 10		_				a					/10				
00+ FD											-					1,580	
PR C 2 14 398.0 - 400.0 400.0 N/Q - 700 700 1628 - 1828 1.7											-					1,359	
FD C 2 2 4 382.0 - 382.0 382.0 - 31 707 - 707 707 1547 - 1547 1.5 PR C 3 4 382.0 - 382.0 382.0 - 31 707 - 707 707 1547 - 1547 1.5 PR C 3 4 382.0 - 378.0 378.0 N/O 700 - 700 700 1985 - 1985 1.9 RS C 2 63 430.0 - 468.0 455.3 35 - 0 1828 1.7 962 346.0 702.0 - 0 1520 - 1520 1.9 FD C 2 6 400.0 - 400.0 400.0 N/O 0 1520 - 1520 1.5 00-500 FD C 2 7 410.0 - 420.0 413.3 N/O 0 1804 - 1953 1.8 00-600 PR C 3 1 4 398.0 - 406.0 404.3 N/O 783 - 783 783 2200 - 2200 2.2 00-750 PR C 3 1 8 376.0 423.0 N/O 783 - 783 783 2200 - 2200 2.2 00-750 PR C 3 1 1390.0 - 390.0 390.0 N/O 722 - 722 722 3120 - 3120 3.1 FD D D 2 10 398.0 - 400.0 398.2 N/O 722 - 722 722 3120 - 3120 3.1 FD D D 3 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1.5 RS D 3 60 390.0 454.0 N/O 788 - 708 708 2400 - 2400 2.4 40+ PR C 3 3 2 375.0 - 375.0 375.0 N/O 708 - 708 708 2400 - 2400 2.4 Adout		RS	С	2	19	702.0 -	702.0	702.0	219		-		0	2352	- 2352	2,352	
PR C 2 4 382.0 - 382.0 382.0 - 31 707 - 707 707 1547 - 1547 1,5 PR C 3 4 378.0 - 378.0 378.0 N/Q 700 - 700 700 1985 - 1985 1,9 PR C 3 4 378.0 - 702.0	400+		0		00	100.0	400.0	400.0	47				•	4.00	4000	4 70	
PR C 3 4 378.0 - 378.0 378.0 N/Q 700 - 700 700 1985 - 1985 1,9 RS C 2 63 430.0 - 468.0 455.3 35 - 0 1828 - 1989 1,9 962 346.0 702.0 641 911 875 2352 rown Steer -400 FD C 2 64 400.0 - 400.0 400.0 N/Q - 0 1520 - 1520 1,5 00-500 FD C 2 27 410.0 - 420.0 413.3 N/Q - 0 1804 - 1953 1,8 00-600 PR C 2 14 398.0 - 406.0 404.3 N/Q 737 - 752 749 2070 - 2071 2,0 PR C 3 1 423.0 - 423.0 423.0 N/Q 783 - 783 783 2200 - 2200 2,2 00-750 PR C 3 18 376.0 - 417.0 396.8 -17 696 - 772 735 2500 - 2585 2,5 50+ PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 rown Helfer -540 FD D 2 10 398.0 - 400.0 398.2 N/Q - 762 726 1307 - 1773 1,5 RS D 2 2 3 300.0 - 300.0 300.0 N/Q - 0 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400										1700	-						
RS C 2 63 430.0 - 468.0 455.3 35 - 0 1828 - 1989 1,9 rown Steer 400 FD C 2 6 400.0 - 400.0 400.0 N/Q - 0 1520 - 1520 1,5 00-500 FD C 2 27 410.0 - 420.0 413.3 N/Q - 0 1804 - 1953 1,8 00-600 PR C 2 14 398.0 - 406.0 404.3 N/Q 737 - 752 749 2070 - 2071 2,0 PR C 3 1 423.0 - 423.0 423.0 N/Q 783 - 783 783 2200 - 2200 2,2 00-750 PR C 3 18 376.0 - 417.0 396.8 -17 696 - 772 735 2500 - 2585 2,5 50+ PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 3,1 rown Helfer -540 FD D 2 10 398.0 - 404.0 384.6 0 679 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 0 1005 - 1005 1,0 RS D 3 60 390.0 - 454.0 439.1 N/Q - 708 708 708 2400 - 2400 2,4 tanutfacturing Steer 40+																1,54	
FD C 2 14 398.0 - 400.0 401.0 N/Q 737 - 752 749 2070 - 2071 2.0 PR C 3 18 376.0 - 417.0 396.8 -17 696 783 783 783 2200 - 2585 2.5 50+ PR C 3 11 390.0 - 423.0 423.0 N/Q 722 - 722 722 3120 - 3120 FD D 2 3 34 360.0 - 423.0 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 FOWN Helfer -540 FD D 2 10 398.0 - 400.0 398.2 N/Q 708 - 762 726 1307 - 1773 1.5 RS D 2 2 300.0 - 300.0 300.0 N/Q 708 - 762 726 1307 - 1773 1.5 RS D 3 3 60 390.0 - 454.0 391.0 N/Q 708 - 708 708 708 2400 - 2400 2.4 Hanufacturing Steer 40+										<i>∞</i> 700	-	700				1,98	
rown Steer -400 FD C 2 6 400.0 - 400.0 400.0 N/Q - 0 1520 . 1520 1,5 00-500 FD C 2 27 410.0 - 420.0 413.3 N/Q - 0 1804 . 1953 1,8 00-600 PR C 2 14 398.0 - 406.0 404.3 N/Q 737 - 752 749 2070 . 2071 2,0 PR C 3 1 423.0 - 423.0 423.0 N/Q 783 - 783 783 2200 . 2200 2,2 00-750 PR C 3 18 376.0 - 417.0 396.8 -17 696 - 772 735 2500 . 2585 2,5 50+ PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 . 3120 FD D 2 10 398.0 - 403.0 598.2 N/Q - 0 1373 . 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 . 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1502 . 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 . 2400 2,4 Inustracturing Steer 40+		RS	С	2				455.3	35		-		0			1,93	
FD C 2 6 400.0 - 400.0 N/Q - 0 1520 - 1520 1,5 00-500 FD C 2 27 410.0 - 420.0 413.3 N/Q - 0 1804 - 1953 1,8 00-600 PR C 2 14 398.0 - 406.0 404.3 N/Q 737 - 752 749 2070 - 2071 2,0 PR C 3 1 423.0 - 423.0 423.0 N/Q 783 - 783 783 2200 - 2200 2,2 00-750 PR C 3 18 376.0 - 417.0 396.8 -17 696 - 772 735 2500 - 2585 2,5 50+ PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 3,1 77 376.0 423.0					962	346.0	702.0			641		911		875	2352		
FD C 2 6 400.0 400.0 400.0 N/Q - 0 1520 - 1520 1,5 00-500 FD C 2 27 410.0 - 420.0 413.3 N/Q - 0 1804 - 1953 1,8 00-600 PR C 2 14 398.0 - 406.0 404.3 N/Q 737 - 752 749 2070 - 2071 2,0 PR C 3 1 423.0 - 423.0 423.0 N/Q 783 - 783 783 2200 - 2200 2,2 00-750 PR C 3 18 376.0 - 417.0 396.8 -17 696 - 772 735 2500 - 2585 2,5 50+ PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 3,1 77 376.0 423.0 696 783 1520 3120 PR D 3 34 360.0 - 400.0 398.2 N/Q - 0 1373 - 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1502 - 1005 1,0 RS D 3 60 390.0 - 454.0 439.1 N/Q - 762 708 708 2400 - 2400 2,4 108 300.0 454.0 70 708 - 708 708 708 2400 - 2400 2,4 108 300.0 454.0 70 708 - 708 708 708 2400 - 2400 2,4 108 300.0 454.0 70 708 - 708 708 708 2400 - 2400 2,4 108 300.0 454.0 70 708 708 708 2400 - 2400 2,4 108 300.0 454.0 70 708 708 708 2400 - 2400 2,4 108 300.0 454.0 70 708 708 708 2400 - 2400 2,4		er															
FD C 2 27 410.0 - 420.0 413.3 N/Q - 0 1804 - 1953 1,8 00-600 PR C 2 14 398.0 - 406.0 404.3 N/Q 737 - 752 749 2070 - 2071 2,0 PR C 3 1 423.0 - 423.0 423.0 N/Q 783 - 783 783 2200 - 2200 2,2 00-750 PR C 3 18 376.0 - 417.0 396.8 -17 696 - 772 735 2500 - 2585 2,5 50+ PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 3,1 77 376.0 423.0 696 783 1520 3120 FD D 2 10 398.0 - 400.0 398.2 N/Q - 0 1373 - 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1005 - 1005 1,0 RS D 3 60 390.0 - 454.0 439.1 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400	0 400	FD X AUS	TRALIA C	2	6	400.0 -	400.0	400.0	N/Q		_		O AUSTRAL!	1520	- 1520	1,520	
FD C 2 27 410.0 - 420.0 413.3 N/Q - 0 1804 - 1953 1,8 00-600 PR C 2 14 398.0 - 406.0 404.3 N/Q 737 - 752 749 2070 - 2071 2,0 PR C 3 1 423.0 - 423.0 423.0 N/Q 783 - 783 783 2200 - 2200 2,2 00-750 PR C 3 18 376.0 - 417.0 396.8 -17 696 - 772 735 2500 - 2585 2,5 50+ PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 3,1 77 376.0 423.0 696 783 1520 3120 FO D D 2 10 398.0 - 400.0 398.2 N/Q - 0 1373 - 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1005 - 1005 1,0 RS D 3 60 390.0 - 454.0 439.1 N/Q - 708 - 708 708 2400 - 2400 2,4 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 Inustracturing Steer 40+	400-500															,	
PR C 2 14 398.0 - 406.0 404.3 N/Q 737 - 752 749 2070 - 2071 2,0 PR C 3 1 423.0 - 423.0 423.0 N/Q 783 - 783 783 2200 - 2200 2,2 00-750 PR C 3 18 376.0 - 417.0 396.8 -17 696 - 772 735 2500 - 2585 2,5 50+ PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 3,1 77 376.0 423.0 696 783 1520 3120 FD D D 2 10 398.0 - 400.0 398.2 N/Q - 0 1373 - 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400		FD	С	2	27	410.0 -	420.0	413.3	N/Q		_		0	1804	- 1953	1,85	
PR C 3 1 423.0 - 423.0 423.0 N/Q 783 - 783 783 2200 - 2200 2,2 00-750 PR C 3 18 376.0 - 417.0 396.8 -17 696 - 772 735 2500 - 2585 2,5 50+ PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 3,1 77 376.0 423.0 696 783 1520 3120 FD D 2 10 398.0 - 400.0 398.2 N/Q - 0 1373 - 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1005 - 1005 1,0 RS D 3 60 390.0 - 454.0 439.1 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400	500-600																
00-750 PR C 3 18 376.0 - 417.0 396.8 -17 696 - 772 735 2500 - 2585 2,5 50+ PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 3,1 77 376.0 423.0 696 783 1520 3120 FD D 2 10 398.0 - 400.0 398.2 N/Q - 0 1373 - 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1005 - 1005 1,0 RS D 3 60 390.0 - 454.0 439.1 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400		PR	С	2	14	398.0 -	406.0	404.3	N/Q	737	-	752	749	2070	- 2071	2,070	
PR C 3 18 376.0 - 417.0 396.8 -17 696 - 772 735 2500 - 2585 2,5 50+ PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 3,1 77 376.0 423.0 696 783 1520 3120 FD D 2 10 398.0 - 400.0 398.2 N/Q - 0 1373 - 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400		PR	C	3	T AUSTRALIA	423.0 -	423.0	423.0	N/Q	783	-	783	783	2200	- 2200	2,200	
PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 3,1 77 376.0 423.0	600-750																
PR C 3 11 390.0 - 390.0 390.0 N/Q 722 - 722 722 3120 - 3120 3,1 77 376.0 423.0 696 783 1520 3120 FO D D 2 10 398.0 - 400.0 398.2 N/Q - 0 1373 - 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1005 - 1005 1,0 RS D 3 60 390.0 - 454.0 439.1 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400		PR	С	3	18	376.0 -	417.0	396.8	-17	696	-	772	735	2500	- 2585	2,52	
FD D 2 10 398.0 - 400.0 398.2 N/Q - 0 1373 - 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400	750+																
FD D 2 10 398.0 - 400.0 398.2 N/Q - 0 1373 - 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1005 - 1005 1,0 RS D 3 60 390.0 - 454.0 439.1 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400		PR	С	3	11	390.0 -	390.0	390.0	N/Q	722	-	722	722	3120	- 3120	3,120	
FD D 2 10 398.0 - 400.0 398.2 N/Q - 0 1373 - 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1005 - 1005 1,0 RS D 3 60 390.0 - 454.0 439.1 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400					77	376.0	423.0			696		783		1520	3120		
FD D 2 10 398.0 - 400.0 398.2 N/Q - 0 1373 - 1800 1,4 PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1005 - 1005 1,0 RS D 3 60 390.0 - 454.0 439.1 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400		fer															
PR D 3 34 360.0 - 404.0 384.6 0 679 - 762 726 1307 - 1773 1,5 RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1005 - 1005 1,0 RS D 3 60 390.0 - 454.0 439.1 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400	u-54U	ED	D	ว	10	308 U	400 O	300 J	NI/O		_		0	1272	_ 1900	1 /1	
RS D 2 2 300.0 - 300.0 300.0 N/Q - 0 1005 - 1005 1,0 RS D 3 60 390.0 - 454.0 439.1 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400 Ianufacturing Steer 40+										670	-	742					
RS D 3 60 390.0 - 454.0 439.1 N/Q - 0 1502 - 1907 1,8 40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400 Itanufacturing Steer										0/9	-	702					
40+ PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400 Ianufacturing Steer 40+											-						
PR C 3 2 375.0 - 375.0 375.0 N/Q 708 - 708 708 2400 - 2400 2,4 108 300.0 454.0 679 762 1005 2400 Identification of the state of the s	F.40	K2	Ŋ	MEAT & LIVES	60	390.0 -	454.0	439.1	IN/Q ESTO		-		U	1502	- 1907	1,81	
108 300.0 454.0 679 762 1005 2400 Manufacturing Steer 40+	54U+	DD	C	2	ว	375 O	375 N	27E 0	NI/O	700	_	709	7∩Ω	2400	- 2400	2 40	
Hanufacturing Steer (1) 40+ WEST & LIVESTOCK AUSTRALIA WEST & LIVESTOCK AUSTRALIA		ΓK	C	3				3/3.0	IN/U		-		700			∠,40	
40+					IUδ	300.0	454.0			0/9		/02		1005	2400		
	Manufactui 540+	ring Stee	RALIA														
		PR	С	3	3	340.0 -	381.0	367.3	N/Q	630	-	706	680	2286	- 3162	2,578	

Click here to view the new and improved Prime Cattle Market Reports

Category Weight	Sale Muscle Fat Prefix Score * Score*				Head Live Weight c/kg				Estimated Carcase Weight c/kg*						Estimated \$/Head			
		<u>a</u>			Low	High	Avg	Change	Low		High	Avg	Low		High	Avg		
	PR	RALIA (; 4	1	280.0 -	280.0	280.0	N/Q	519	-	519	519	2240	-	2240	2,240		
				4	280.0	381.0			519		706		2240		3162			
Cows																		
0-400																		
	FD) 2	2 46	302.0 -	318.0	310.2	N/Q		-		0	992	-	1240	1,063		
	PR			2 17	318.0 -	342.0	332.1	18	691	-	743	722	1208	/	1231	1,222		
	PR) MEAZ	LINESTO 2	372.0 -	372.0	372.0	N/Q	809	-	809	809	1414	MEAT 8	1414	1,414		
	RS) 2	2 34	312.0 -	346.0	321.0	N/Q		-		0	1217	-	1246	1,224		
400-520																		
	PR	[) 2	2 17	332.0 -	340.0	334.8	16	708	-	722	717	1477	-	1683	1,550		
	PR	RALIA [) 3	95	345.0 -	368.0	359.7	8	690	-	750	723	1553	-	1746	1,660		
	PR) 4	2	373.0 -	373.0	373.0	2	777	-	777	777	1846	-	1846	1,846		
	RS) 2	205	318.0 -	366.0	357.3	25		-		0	1288	-	1574	1,532		
520+																		
	PR) 3	3 23	351.0 -	369.0	362.1	1	702	-	769	744	1895	-	2202	1,991		
	PR) 4	85	372.0 -	383.0	378.6	6	744	-	792	762	1998	-	2375	2,131		
				526	302.0	383.0			690		809		992		2375			
5.11																		
Bulls 0-450																		
0-430	RS		; 2	2 61	436.0 -	600.0	555.4	-4		_		0	1461	_	1569	1,517		
	RS	a [650.0 -		657.2	51		_		03	1202	_	1268	1,242		
450-600	TOCK AUST	RALIA	, 2		000.0	OOO.O	USTRALIA 7.2	31				CTOCK AUSTRALI	1202		1200	1,272		
MEAT & L	PR	(, 2	2 3	350.0 -	350.0	350.0	N/Q	636	_	636	636	2030	_	2030	2,030		
600+																_,,,,,		
	PR		; 2	2 33	345.0 -	374.0	351.8	-1	627	_	680	640	2381	_	3067	2,709		
	PR	(354.0 -	370.0	364.3	9	644	_	673	662	3616	_	3894	3,737		
				125	345.0	668.0			627		680	-	1202		3894	USTRALIA		
				& LIVESTOCK . 20	0.0.0	300.0			Christ		500							

DA - Dairy, FD - Feeder, GF - Grainfed, PR - Processor, LE - Live Export, PC - Pastoral Cattle, PT - PTIC, RS - Restocker

Disclaimer:

© MLA 2021. No part of this publication may be reproduced in any form or by any means without prior written permission of MLA. MLA makes no representations and to the extent permitted by law excludes all warranties in relation to the information contained in this publication. MLA is not liable to you or to any third party for any losses, costs or expenses, including any direct, incidental, consequential, special or exemplary damages or lost profit, resulting from any use or misuse of the information contained in this publication. Information contained in this publication has been obtained from a variety of third party sources which have not been verified by MLA.









© 2021 Meat and Livestock Australia Limited Page: 3 of 3